

Type/power output (+10°C):	SelfTec 10 W/m	SelfTec 16 W/m	SelfTec DW 10 W/m	SelfTec Pro 10 W/m	SelfTec Pro 20 W/m	SelfTec Pro 33 W/m
Power supply:	230 V ~ 50/60 Hz					
External dimension of cable:	~ 6 X 8 mm		~ 6 X 8 mm	~ 6 X 11 mm		~ 6 X 13 mm
Min. installation temperature:	-25 °C					
Max. working temperature:	65 °C					
Max. exposure temperature, power-on, 1000h – cumulative:	65 °C			85 °C		
Type of heating cable:	Selfregulating, conductor screen, single-side power supply					
Conductor, tin-coated copper:	0.6 mm <sup>2</sup>	0.6 mm <sup>2</sup>	0.6 mm <sup>2</sup>	1.0 mm <sup>2</sup>	1.0 mm <sup>2</sup>	1.25 mm <sup>2</sup>
Insulation:	Modified polyolefin					
Outer sheath:	UV resistant, halogen free polyolefin		LDPE, certified for drinking water applications	UV resistant, halogen free polyolefin		
Resistance tolerance:	+/- 5 %					
Min. bending radius:	3.5 D					
Protection:	IPX 7					
Max. cable length per circuit (Max. circuit-breaker, C-type):	100 (10A)	72 (10A)	60 (10A)	150 (16A)	110 (16A)	108 (30A)
Product certificates:	B, GOST-R			B		
Certificate of ISO 9001	IQNET, PCBC					
Product mark:	CE					